

PART 1: GENERAL

1.01 Scope Of Standard

- A. This standard provides general guidance concerning the specific preferences of the Sam Houston State University for roofing systems.
- B. SHSU recognizes that project conditions and requirements vary, thus precluding the absolute adherence to the items identified herein in all cases. However, unless there is adequate written

**SAM HOUSTON STATE UNIVERSITY
DIVISION 07 THERMAL & MOISTURE PROTECTION**

3. S

3. If existing roof is mechanically fastened, determine how to remove roof and methods to repair substrate.
 - B. Test for asbestos, lead, and asphaltic substances whose removal may require abatement or special environmental considerations.
 - C. Inspect existing skylights and report to SHSU project representative whether it would be prudent to include skylight re-work with roof repairs. Likewise, for roof scuttle and other rooftop accessories.
 - D. Remove existing roof to substrate unless approved by SHSU. Never remove more roof than can be dried-in prior to completion of day's work or in the event of rain.
 - E. Provide for substrate repair/replacement in Base Bid (by assumed quantities or percentages, and unit prices, if necessary).
 - F. Replace all nailers. Provide unit prices with bid to allow existing nailers to remain if determined to be satisfactory.
 - G. Re-use of existing counter flashing is permissible if SHSU project representative agrees. Verify height of finished roof and include repair in bid.
9-1631711-2016-524(p)-3.9(pku3.3(o c)-3.9(c)-3.9(e)-3.o a)-3.9